



(43) International Publication Date
15 September 2005 (15.09.2005)


PCT

(10) International Publication Number
WO 2005/085582 A1

- (51) **International Patent Classification⁷:** **E21B 10/66, 7/20**
 (21) **International Application Number:** **PCT/SE2005/000219**
 (22) **International Filing Date:** 18 February 2005 (18.02.2005)
 (25) **Filing Language:** English
 (26) **Publication Language:** English
 (30) **Priority Data:**
 0400597-1 10 March 2004 (10.03.2004) SE
 (71) **Applicant (for all designated States except US):** **SANDVIK INTELLECTUAL PROPERTY AB [SE/SE]; S-811 81 Sandviken (SE).**
 (72) **Inventor; and**
 (75) **Inventor/Applicant (for US only):** **RAVAT, Pierre [FR/FR]; 4 Rue du Puits Fattin, F-01360 Loyettes (FR).**
 (74) **Agent:** **CARLSSON, Lars-Åke: Sandvik AB, S-811 81 Sandviken (SE).**
 (81) **Designated States (unless otherwise indicated, for every kind of national protection available):** AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
 (84) **Designated States (unless otherwise indicated, for every kind of regional protection available):** ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO,

[Continued on next page]

- (54) Title: SINGLE PASS DRILLING APPARATUS, USE A ONE -PIECE DRILL BIT, METHOD AND ROCK BOLT FOR SINGLE PASS ROCK BOLTING.



(57) Abstract: The present invention relates to a single pass drilling apparatus, a rock bolt, use of a drill bit and a method for single pass rock bolting for reinforcement and stabilization of excavations. The single pass drilling apparatus comprises an elongated drill steel (11) having a leading (12) and a trailing end (13) with reference to a drilling direction (F). The leading end (12) has a connection portion. A one-piece drill bit (16) is utilized having rock machining means (17,18;17'18'). The drill bit is connectable to the drill steel. The single pass drilling apparatus (10) further comprises a rock bolt (21;22;23;24) adapted to at least partially enclose the drill steel (11). The greatest diametrical dimension (DB) of the drill bit (16) is smaller than the smallest diametrical dimension (DI) of the rock bolt.



SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— with international search report